

6 CYLINDERS IN LINE - DIESEL CYCLE

272 kW (370 HP) @ 2800 rpm (A1)

243 kW (330 HP) @ 2800 rpm (B)

199 kW (270 HP) @ 2800 rpm (C)

Specifications

Thermodynamic cycle		Diesel 4 stroke
Air intake		TCA
Arrangement		6L
Bore x Stroke	mm	102 x 120
Total displacement	l	5.9
Valves per cylinder	n.	4
Cooling system		liquid
Direction of rotation (viewed facing flywheel)		CCW
Engine management		by EDC (Electronic Diesel Control)
Injection system		Electronic Common Rail (E.C.R.)

Electrical system

Voltage	V	12
---------	---	----

Standard configuration

Flywheel housing	type	SAE 3
Flywheel size	inch	11.5
Air filter		rear side
Turbocharger		Fixed Geometry (water cooled) Turbo with Aftercooler (TCA)
Heat exchanger		tube type
Exhaust gas - water mixer		-
Water charge tank		included
Fuel filter	n.	1 - left side
Fuel prefilter		included (loose)
Fuel pump		included
Oil filter	n.	1 - right side
Oil sump		aluminium
Oil vapours blow-by circuit		rear
Oil heat exchanger		built in the crankcase
Oil filler		by cylinder head cover
Starting motor		12V - 3kW
Alternator		12V - 90A
Engine stop device		by electronic central unit
Electrical wiring		with negative to ground connection
Painting	color	white "ICE"

Not included in the standard configuration

Battery - minimum capacity recommended		120 Ah
Battery - minimum cold cranking capacity recommended		900 A


FPT OFFERS THE WIDEST AVAILABILITY OF ENGINE BUILD OPTIONS TO CUSTOMER SPECIFIC REQUIREMENTS WITHIN THE ENGINE SUPPLY. TO FIND OUT MORE ABOUT THE CONFIGURATIONS AND ACCESSORIES WHICH ARE AVAILABLE, CONTACT THE FPT SALES NETWORK.

N60 370

Rating type		A1	B	C
Maximum power [*]	kW(HP)	272 (370)	243 (330)	199 (270)
At speed	rpm	2800	2800	2800
Maximum no load governed speed at max rating	rpm		3000	
Minimum idling speed	rpm		600	
Mean piston speed at rated speed	m/s		11.2	
BMEP at max power	kg/cm ²	23.3	21.8	19.8
Specific fuel consumption at full load (best value)	g/kWh @ rpm		207 @ 2000	
Oil consumption at max rating	(% of fuel cons.)		≤ 0.2	
Minimum starting temperature without auxiliaries	°C		-10°	
Oil and oil filter maintenance interval for replacement	hours		600	

* Net Power at flywheel according to ISO 8665, after 50 hours running, Fuel Diesel EN 590. Power tolerance 5%.


Test conditions: 25 °C air temperature, 100 kPa atmospheric pressure, 30 % relative humidity .



A1 = High performance crafts:
 Full throttle operation restricted within 10% of total use period.
 Cruising speed at engine rpm <90% of rated speed setting - Maximum useage 300 hours per year.

B = Light duty:
 Full throttle operation restricted within 10% of total use period.
 Cruising speed at engine rpm <90% of rated speed setting - Maximum useage 1500 hours per year.

C = Medium duty:
 Full throttle operation <25% of use period.
 Cruising speed at engine rpm <90% of rated speed setting - Maximum useage 3000 hours per year.



L1 = 1072 mm.
 W = 739 mm.
 H = 778 mm.
 Dry weight (without marine gear) = 595 kg.