

**SPECIFICATIONS**

|                                                                       |                              |                |
|-----------------------------------------------------------------------|------------------------------|----------------|
| Thermodynamic Cycle                                                   | Diesel 4 stroke              |                |
| Air Handling                                                          | TC                           |                |
| Arrangement                                                           | 6L                           |                |
| Bore x Stroke (mm)                                                    | 104 X 132                    |                |
| Total Displacement (l)                                                | 6.7                          |                |
| Valves per cylinder (n°)                                              | 2                            |                |
| Injection System                                                      | M                            |                |
| Speed governor                                                        | mechanical                   |                |
| Cooling System                                                        | liquid (water - paraflu 50%) |                |
| Direction of Rotation (viewed facing flywheel)                        | CCW                          |                |
| Oil specifications                                                    | ACEA E3-E5                   |                |
| Oil consumption                                                       | <0.1% of fuel consumption    |                |
| Fuel specifications                                                   | EN 590                       |                |
| Oil and oil filter maintenance interval for replacement [***] (hours) | 600                          |                |
| Specific fuel consumption at:                                         | <b>1500</b>                  | <b>1800</b>    |
| - Stand-By l/h (g/kWh)                                                | -                            | -              |
| - 100% load l/h (g/kWh)                                               | 28.8 ( 212.5 )               | 33.9 ( 216.3 ) |
| - 80% load l/h (g/kWh)                                                | 23.2 ( 214 )                 | 27.5 ( 219.4 ) |
| - 50% load l/h (g/kWh)                                                | 14.6 ( 216.3 )               | 18.3 ( 233.2 ) |
| ATB (without canopy) (°C)                                             | 51                           | 49             |
| Coolant capacity: engine + radiator (l)                               | ~ 40.5                       |                |
| Coolant capacity: engine only (l)                                     | ~ 10.5                       |                |
| Lube oil total system capacity including pipes, filters etc. (l)      | ~ 17.2                       |                |
| Electric system (isolated return)                                     | 12                           |                |
| Starting batteries: recommended capacity (Ah)                         | 1 x 100                      |                |
| Discharge Current (EN50342) A                                         | 650                          |                |
| Cold starting: without preheating (°C)                                | -10                          |                |
| Cold starting: with preheating (°C)                                   | -25                          |                |

**WEIGHT AND DIMENSIONS**

|                    |                   |
|--------------------|-------------------|
| Dimensions (LxWxH) | 1697 X 789 X 1318 |
| Dry Weight         | Kg 610            |

**PERFORMANCE**

| Ratings <sup>1</sup>         | 1500 rpm |          | 1800 rpm |          |
|------------------------------|----------|----------|----------|----------|
|                              | PRIME    | STAND-BY | PRIME    | STAND-BY |
| Rated Power kWm <sup>2</sup> | 110      | 121      | 126      | 138      |

<sup>1</sup>) Ratings in accordance with ISO 8528. For duty at temperature over 40°C and/or altitude over 1000 meters must be considered a power derating factor. Contact the FPT sales organization.

<sup>2</sup>) Net power at flywheel available after 50 hours running with a ±3% tolerance.

**PRIME POWER:** The prime power is the maximum power available with varying loads for an unlimited number of hours. The average power output during a 24h period of operation must not exceed 80% of the declared prime power between the prescribed maintenance intervals and at standard environmental conditions. A 10% overload is permissible for 1 hour every 12 hours of operation.

**STAND-BY POWER:** The stand-by power is the maximum power available for a period of 500 hours/year with a mean load factor of 90% of the declared stand-by power. No kind of overloads is permissible for this use.

**CONTINUOUS POWER:** Contact the FPT sales organization.

**Legend**

| Arrangement                              | Air Handling                                                                         | Injection System                                                                 | Emission Standard    |
|------------------------------------------|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|----------------------|
| L (in line)<br>V (90° "V" configuration) | TAA (Turbocharged with aftercooler)<br>TC (Turbocharged)<br>NA (Naturally Aspirated) | M (Mechanical)<br>ECR (Electronic Common Rail)<br>EUI (Electronic Unit Injector) | I-EGR (Internal EGR) |

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

FPT INDUSTRIAL OFFERS THE WIDEST AVAILABILITY OF ENGINE BUILD OPTIONS TO CUSTOMER SPECIFIC REQUIREMENTS WITHIN THE ENGINE SUPPLY. TO FIND OUT MORE ABOUT THE CONFIGURATIONS AND ACCESSORIES WHICH ARE AVAILABLE

[www.fptindustrial.com](http://www.fptindustrial.com)



Publication P4A06N007E - 01.12  
Specifications subject to change without notice.  
Illustrations may include optional equipment.

## STANDARD CONFIGURATION

FPT engine N67 SM1 equipped with:

- Mounted radiator
- Mounted belt driven pusher fan
- Fan guard
- Mounted air filter with replaceable cartridges
- Fuel filter
- Primary fuel filter/water separator
- Replaceable oil filter
- Front engine mounting brackets
- Flywheel housing SAE3 and flywheel 11" 1/2
- Re-directable exhaust gas elbow
- Recircled oil breather system
- Oil dipstick
- HWT and LOP sensors
- 12Vdc electrical system
- User's handbook

THE ENGINE IS SUPPLIED WITHOUT LIQUIDS

## OPTIONAL EQUIPMENT

On request the engine can be supplied with:

- Oil drain pump
- Oil drain valve
- 120/230 Volt water jacket heater
- WT and OP sensors for gauges
- Low water level sensor
- Turbo and exhaust gas guards
- Exhaust gas flexible joint
- 24Vdc electrical system
- Front radiator guard
- Electronic speed governor

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)