

## SPECIFICATIONS

Thermodynamic Cycle	Diesel 4 stroke
Air Handling	TAA
Arrangement	6L
Bore x Stroke (mm)	117 X 135
Total Displacement (l)	8.7
Valves per cylinder (n°)	4
Cooling System	liquid
Direction of Rotation (viewed facing flywheel)	CCW
Compression ratio	16:1
Injection System	ECR

## PERFORMANCE

Rated power [*] (kW (HP) @ rpm)	260 ( 354 ) @ 2100
Peak torque (Nm (kgm) @ rpm)	1500 ( 153 ) @ 1400
High idle speed (rpm)	2300
Low idle speed (rpm)	± 800
Minimum starting temperature without auxiliaries (°C)	-15 °
Oil and oil filter maintenance interval for replacement [***] (hours)	600

## STANDARD CONFIGURATION

Flywheel housing (type)	SAE 1 - aluminium
Flywheel size (inch)	14"
Intake manifold location	right side / outwards
Exhaust manifold location	-
Turbocharger	fixed geometry
Turbocharger location	middle / left side
Fan transmission ratio	1.03:1
Distance between fan - crankshaft centers (mm)	X = 0 Y = 250
Fuel filter (n°)	1 - right side
Fuel prefilter	included, supplied loose
Fuel Pump	high pressure pump (H.P.P.)
Oil filter (n°)	ecological cartridge - left side
Oil sump	suspended sheet steel / central slump
Oil vapours blow-by circuit	close case ventilation
Oil heat exchanger	incorporated into the block
Oil filler	on valve cover
Lift pump	-
Starter	24V - 4.5kW
Alternator	24V - 90A
Engine stop device	by electronic control unit
Wiring harness	interface wiring loom with accessories
Painting color	grey

## WEIGHT AND DIMENSIONS



## NOT INCLUDED IN STANDARD CONFIGURATION

Power Take Off (PTO)	-
PTO - transmission ratio	1.1:1
PTO - maximum available torque	SAE A 120 Nm (9 teeth ANSI B92,1) SAE B 120 Nm (13 teeth ANSI B92,1) - 180 Nm (grooved DIN 5482) SAE 2B 180 Nm (15 teeth ANSI B92,1)
Battery - minimum capacity recommended [*] (Ah)	180Ah (24V)
Battery - minimum cold cranking capacity recommended [*] (A)	800A (24V)

[\*] Power at flywheel according to 2004/26 EC (without fan), after 50 hours running, 3% tolerance, fuel Diesel EN 590.  
[\*\*] Oil type: ACEA E3 - E5.

## Legend

<b>Arrangement</b> L (in line)	<b>Air Handling</b> TAA (Turbocharged with aftercooler) TC (Turbocharged) NA (Naturally Aspirated)	<b>Turbocharger</b> WG (Wastegate) VGT (Variable Geometry Turbocharger) TST (Twin Stage Turbocharge)	<b>Injection System</b> M (Mechanical): ECR (Electronic Common Rail) EUI (Electronic Unit Injector)	<b>Emission Standard</b> EEV (Enhanced Environmentally friendly Vehicle)	<b>Exhaust System</b> EGR (Exhaust Gas Recirculation) SCR (Selective Catalytic Reduction)
-----------------------------------	---	---	--	---	---

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM



FPT INDUSTRIAL OFFERS THE WIDEST AVAILABILITY OF ENGINE BUILD OPTIONS TO CUSTOMER SPECIFIC REQUIREMENTS WITHIN THE ENGINE SUPPLY. TO FIND OUT MORE ABOUT THE CONFIGURATIONS AND ACCESSORIES WHICH ARE AVAILABLE

[www.fptindustrial.com](http://www.fptindustrial.com)

