

OFF ROAD Power Units CURSOR 13

407 kW (554 HP) @ 2100 rpm Stage V - Tier 4 Final

CURSOR 13

POWER & TORQUE

CURSOR 13

SPECIFICATIONS

No. of cylinders / valves		6L / 4
Injection System		COMMON RAIL 2200 bar
Turbocharger		WG
Displacement	liters	12.9
Bore x Stroke	millimeters	135 x 150
Rated power	kW (HP) @ rpm	407 (554) @ 2100
Max Torque	Nm @ rpm	2400 @ 1400
ATS		DOC-SCRoF
Certification		Stage V - Tier 4 Final

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	- x - x -
Dry Weight	Kg	-

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DOC (Diesel Oxidation Catalyst)

DPF (Diesel Particulate Filter)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



