


SPECIFICATIONS

No. of cylinders / valves	4L / 4	
Injection System	COMMON RAIL 1800 bar	
Turbocharger	WG	
Displacement	liters	3.6
Bore x Stroke	millimeters	102 x 110
Max power	kW (HP) @ rpm	105 (143) @ 2300
Max Torque	Nm @ rpm	600 @ 1500
ATS	Compact HI-eSCR2	
Certification	Stage V	

WEIGHT AND DIMENSIONS


Dimensions (L x W x H)	mm	1199 x 758 x 1376
Dry Weight	Kg	420

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

POWER & TORQUE



POWER UNITS

Do you want to know more?



LEGEND

Air Handling

- TCA (Turbocharged with aftercooler)
- TC (Turbocharged)
- NA (Naturally Aspirated)

Turbocharger

- WG (Wastegate)
- VGT (Variable Geometry Turbocharger)
- TST (Twin Stage Turbocharge)

Exhaust System

- EGR (Exhaust Gas Recirculation)
- SCR (Selective Catalytic Reduction)
- DOC (Diesel Oxidation Catalyst)
- DPF (Diesel Particulate Filter)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

